MUSHOR Technology مشور تكنولوجي
VALUE ADDED DISTRIBUTOR

Authorized distributor of **b2 electronics** in the Kingdom of Saudi Arabia

B2 ELECTRONICS

HVA34

VLF High Voltage Test Set

The b2 electronics HVA34 is a compact, portable VLF test set with a robust design and a strong power-to-weight ratio for routine cable testing in the field. It assesses the condition of medium-voltage cables up to 15 kV in accordance with IEEE 400.2, and besides VLF testing with sine and square wave and DC testing it performs sheath testing and sheath fault location (an additional sheath fault locator is needed).

It can test cables more than 3 km long at 24 kVrms and 0.1 Hz (250 pF/m, 0.9 µF load). The output stays purely sinusoidal over the entire power range, operating time has no thermal limit, and the dry system with non-arcing contacts needs no oil changes. Results are stored on the unit and downloaded via USB for reporting with b2 ControlCenter, so no laptop is needed on site.



OUTPUT VOLTAGE	OUTPUT LOAD	CABLE RATING	WEIGHT
34 kVpeak / 24 kVrms	**0.9 µF @ 24 kVrms**	**Up to 15 kV**	**20 kg**

KEY FEATURES

- Max 34 kVpeak / 24 kVrms output
- For MV cables up to 15 kV (IEEE 400.2)
- VLF sine and square wave, DC, sheath and vacuum bottle tests
- Load-independent pure sinusoidal output
- Continuous operation, no thermal limitation
- Electronic and mechanical discharge, 12 kV backfeed protection
- Breakdown and load detection, real-time oscilloscope display
- Dry system, no oil changes
- Expandable with b2 PD, TD or PDTD diagnostics such as the PDTD68

Contact Mushor Technology — Authorized b2 electronics distributor in Saudi Arabia

CALL **920031385**
WHATSAPP **+966 50 025 4300**
EMAIL **info@mushor.com**
WEB **mushor.com**

Riyadh – King Fahad Road – Al Washam Tower · Branches: Olaya · Al Khobar · Jeddah

TECHNICAL DATA — HVA34

Output voltage	VLF sine 0–34 kVpeak / 0–24 kVrms; DC −34 to +34 kV; VLF square 0–34 kV; sheath test 0–10 kV (negative)
Frequency	0.01–0.1 Hz, setting resolution 0.01 Hz
Output load	0.9 µF @ 0.1 Hz @ 24 kVrms
Test capability	Cables more than 3 km (250 pF/m) at 24 kVrms, 0.1 Hz
Output current	AC 20 mArms max., DC 32 mA max.; sheath test trip 0.1–5 mA; sheath fault location 17 mA max.
Test types	VLF withstand, DC, sheath test, sheath fault location, vacuum bottle test
Compliance	IEEE 400.2; DIN VDE 0276-620 (CENELEC HD 620 S2), DIN VDE 0276-621 (CENELEC HD 621 S1); IEC 60502-2 / IEC 60229
Safety	Dual Discharge Device, 12 kV backfeed protection (50/60 Hz), external interlock, key switch
Data	USB, RS232; memory for 50 reports and 40 test sequences; b2 ControlCenter and HVA ControlCenter included
Power supply	110–240 V, 50/60 Hz, 1,100 VA
Operating temperature	−10 to +50 °C
Dimensions / weight	430 × 250 × 360 mm / 20 kg

DIAGNOSTICS & OPTIONS

Suggested diagnostics	b2 PDTD68 (PD & TD), b2 TD60-MC (Tan Delta)
Optional accessory	Transport case
Software	b2 ControlCenter included; HVA ControlCenter included

Technical data from b2 electronics datasheet DHV1443 Rev03. Specifications are subject to change by the manufacturer without notice.

Contact Mushor Technology — Authorized b2 electronics distributor in Saudi Arabia

CALL **920031385**
WHATSAPP **+966 50 025 4300**
EMAIL **info@mushor.com**
WEB **mushor.com**

Riyadh – King Fahad Road – Al Washam Tower · Branches: Olaya · Al Khobar · Jeddah